

# EASY FLOW<sup>®</sup> FIRE PROTECTION SPRINKLER PIPES



A leading European producer of steel pipes, Borusan Mannesmann is the choice of clients across Europe, the US and Canada for industrial and residential fire protection sprinkler system pipes.

Factory Mutual approved, Underwriters Laboratories and Canadian UL listed, ASTM A 795 and ASTM A 53 production standard Borusan Mannesmann sprinkler pipes... To enhance the safety of your projects with the professional service and high quality assurance of Borusan Mannesmann, known all over the world.

# EASY FLOW<sup>®</sup> SPRINKLER PIPES

## PRODUCT OPTIONS

NOMINAL SIZES (INCHES)	NOMINAL WALL (INCHES)	WEIGHT LB/FT	STANDART LENGTH	THREADED CORROSION RESISTANCE RATIO
1/2"	0.109	0.85	21	1
3/4"	0.083	0.86	21	1
3/4"	0.113	1.13	21	1
1"	0.109	1.41	21	1
1"	0.133	1.68	21	1
1 1/4"	0.109	1.81	21	1
1 1/4"	0.140	2.27	21	1
1 1/2"	0.084	1.62	21	1
1 1/2"	0.109	2.09	21	1
1 1/2"	0.145	2.72	21	1
2"	0.084	2.05	21	1
2"	0.109	2.64	21	1
2"	0.154	3.66	21	1
2 1/2"	0.086	2.55	21	1
2 1/2"	0.120	3.53	21	1
2 1/2"	0.203	5.80	21	1
3"	0.093	3.38	21	1
3"	0.120	4.34	21	1
3"	0.216	7.58	21	1
4"	0.120	5.62	21	1
4"	0.237	10.80	21	1
5"	0.134	7.78	21	1
5"	0.258	14.63	21	1
6"	0.134	9.30	21	1
6"	0.280	18.99	21	1
8"	0.148	13.40	21	1
8"	0.188	16.96	21	1
8"	0.322	28.58	21	1
10"	0.188	21.23	21	1
10"	0.365	40.52	21	1
12"	0.188	25.28	21	1
12"	0.375	49.61	21	1

## TECHNICAL SPECIFICATIONS

- Grooved or ready to groove,
- FM approved,
- UL/C-UL Listed,
- NSF certified,
- Selection of Schedule 40, Schedule 10 and Schedule 7 material,
- ASTM A 795 and ASTM A 53 production standards,
- Tight tolerances,
- Consistent roundness,
- Consistent wall thickness,
- Consistent straightness,
- Standard length 21 feet,
- Weldable,
- Pressure tested,
- Corrosion resistance ratio of 1.0,
- Reliable high steel quality,
- Galvanised or shop primer coated (black or red).

